

Linsenkopfschrauben mit Innensechskant & Flansch

ISO 7380-2


Hinweis: Artikel mit Teilgewinde werden, je nach Hersteller, auch mit Gewinde bis annähernd Kopf geliefert

Optional: Stahl blank (schwarz) 10.9 -ST

Typ Stahl 10.9 verzinkt	Typ Edelstahl* A2	D	L	B (min)
Dk=6,9; K=1,65; S=2				
7380-2-M3x8	7380-2-M3x8 ES	M 3	8	*
7380-2-M3x10	7380-2-M3x10 ES	M 3	10	*
7380-2-M3x12	7380-2-M3x12 ES	M 3	12	*
7380-2-M3x16	7380-2-M3x16 ES	M 3	16	*
7380-2-M3x20	7380-2-M3x20 ES	M 3	20	*
Dk=9,4; K=2,2; S=2,5				
7380-2-M4x8	7380-2-M4x8 ES	M 4	8	*
7380-2-M4x10	7380-2-M4x10 ES	M 4	10	*
7380-2-M4x12	7380-2-M4x12 ES	M 4	12	*
7380-2-M4x16	7380-2-M4x16 ES	M 4	16	*
7380-2-M4x20	7380-2-M4x20 ES	M 4	20	*
7380-2-M4x25	7380-2-M4x25 ES	M 4	25	*
7380-2-M4x30	7380-2-M4x30 ES	M 4	30	20
Dk=11,8; K=2,75; S=3				
7380-2-M5x8	7380-2-M5x8 ES	M 5	8	*
7380-2-M5x10	7380-2-M5x10 ES	M 5	10	*
7380-2-M5x12	7380-2-M5x12 ES	M 5	12	*
7380-2-M5x16	7380-2-M5x16 ES	M 5	16	*
7380-2-M5x20	7380-2-M5x20 ES	M 5	20	*
7380-2-M5x25	7380-2-M5x25 ES	M 5	25	*
7380-2-M5x30	7380-2-M5x30 ES	M 5	30	22
7380-2-M5x35	7380-2-M5x35 ES	M 5	35	22
7380-2-M5x40	7380-2-M5x40 ES	M 5	40	22
Dk=13,6; K=3,3; S=4				
7380-2-M6x8	7380-2-M6x8 ES	M 6	8	*
7380-2-M6x10	7380-2-M6x10 ES	M 6	10	*
7380-2-M6x12	7380-2-M6x12 ES	M 6	12	*
7380-2-M6x16	7380-2-M6x16 ES	M 6	16	*
7380-2-M6x20	7380-2-M6x20 ES	M 6	20	*
7380-2-M6x25	7380-2-M6x25 ES	M 6	25	*
7380-2-M6x30	7380-2-M6x30 ES	M 6	30	*
7380-2-M6x35	7380-2-M6x35 ES	M 6	35	24
7380-2-M6x40	7380-2-M6x40 ES	M 6	40	24
7380-2-M6x45	7380-2-M6x45 ES	M 6	45	24
7380-2-M6x50	7380-2-M6x50 ES	M 6	50	24

* Gewinde bis annähernd Kopf

Typ Stahl 10.9 verzinkt	Typ Edelstahl* A2	D	L	B (min)
Dk=17,8; K=4,4; S=5				
7380-2-M8x10	7380-2-M8x10 ES	M 8	10	*
7380-2-M8x12	7380-2-M8x12 ES	M 8	12	*
7380-2-M8x16	7380-2-M8x16 ES	M 8	16	*
7380-2-M8x20	7380-2-M8x20 ES	M 8	20	*
7380-2-M8x25	7380-2-M8x25 ES	M 8	25	*
7380-2-M8x30	7380-2-M8x30 ES	M 8	30	*
7380-2-M8x35	7380-2-M8x35 ES	M 8	35	*
7380-2-M8x40	7380-2-M8x40 ES	M 8	40	28
7380-2-M8x45	7380-2-M8x45 ES	M 8	45	28
7380-2-M8x50	7380-2-M8x50 ES	M 8	50	28
7380-2-M8x55	7380-2-M8x55 ES	M 8	55	28
7380-2-M8x60	7380-2-M8x60 ES	M 8	60	28
Dk=21,9; K=5,5; S=6				
7380-2-M10x20	7380-2-M10x20 ES	M 10	20	*
7380-2-M10x25	7380-2-M10x25 ES	M 10	25	*
7380-2-M10x30	7380-2-M10x30 ES	M 10	30	*
7380-2-M10x35	7380-2-M10x35 ES	M 10	35	*
7380-2-M10x40	7380-2-M10x40 ES	M 10	40	*
7380-2-M10x45	---	M 10	45	32
7380-2-M10x50	7380-2-M10x50 ES	M 10	50	32
7380-2-M10x55	---	M 10	55	32
7380-2-M10x60	7380-2-M10x60 ES	M 10	60	32
Dk=26; K=6,6; S=8				
7380-2-M12x16	---	M 12	16	*
7380-2-M12x20	---	M 12	20	*
7380-2-M12x25	---	M 12	25	*
7380-2-M12x30	---	M 12	30	*
7380-2-M12x35	---	M 12	35	*
7380-2-M12x40	---	M 12	40	*
7380-2-M12x45	---	M 12	45	*
7380-2-M12x50	---	M 12	50	*
7380-2-M12x60	---	M 12	60	36



Bestellbeispiel: 7380-2-M3x8 **

Standardtyp

Kennzeichen der Optionen:

Stahl blank (schwarz) 10.9-ST

Ringschrauben

DIN 580 & ähnlich DIN 580

Optional: Stahl blank -ST, Edelstahl A4 -ES4A, Edelstahl A4 gegossen (ähnlich DIN) -ESB

Typ Stahl verzinkt	Typ Edelstahl* A2	D	D1	D2	D3	H	K	L	Neenrtagfähigkeit (WLL) im geradem Zug*
580-M6	580-M6 ES	M 6	20	36	20	36	8	13,0	75 kg
580-M8	580-M8 ES	M 8	20	36	20	36	8	13,0	140 kg
580-M10	580-M10 ES	M 10	25	45	25	45	10	17,0	230 kg
580-M12	580-M12 ES	M 12	30	54	30	53	12	20,5	340 kg
580-M14	---	M 14	35	63	35	62	14	27,0	490 kg
580-M16	580-M16 ES	M 16	35	63	35	62	14	27,0	700 kg
580-M18	---	M 18	40	72	40	71	16	30,0	850 kg
580-M20	580-M20 ES	M 20	40	72	40	71	16	30,0	1200 kg
580-M22	---	M 22	50	90	50	90	20	36,0	1400 kg
580-M24	580-M24 ES	M 24	50	90	50	90	20	36,0	1800 kg
580-M30	---	M 30	65	108	60	109	24	45,0	3200 kg
580-M36	---	M 36	75	126	70	128	28	54,0	4600 kg

* gilt nicht für Edelstahl A4 gegossen (ähnlich DIN)

Bestellbeispiel: 580-M6 **

Standardtyp

Kennzeichen der Optionen:

Stahl blank-ST

Edelstahl A4-ES4A

Edelstahl A4 gegossen (ähnlich DIN)-ESB

